



SPECIFICATIONS
AKCV30
 CENTRAL VACUUMS

CENTRAL VACUUM POWER UNIT

- **Motor**
Two stage 120 volt, double ball bearing with tangential bypass discharge and thermoset fan end bracket. 9.7 amps.
- **Power Unit Body**
Durable textured powder coated all steel body.
- **Performance**
CFM at 2" opening: 112
Water Lift: 106"
Air Watts: 409
- **Collection**
5 gallon disposable collection bag.
- **Recommended Home Size**
Homes up to 2,800 square feet.
- **Mounting**
Includes metal mounting bracket and an extra utility inlet. Unit does not exhaust to the outside.
- **Shipping Information**
UPC: 0-83162-
Shipping Weight: lbs.



PROJECT							ARCHITECT			
LOCATION							ENGINEER			
CONTRACTOR							SUBMITTED BY			DATE
FAN NUMBER	MODEL NUMBER	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY	OPTIONAL EQUIPMENT & REMARKS	



U.S.: 820 Lincoln Drive
 West Chester, Pennsylvania 19380-4466
 Tel: (610) 692-7400 • 877-304-3785
 Fax: (610) 696-8048

Canada: 110 Glidden Road
 Brampton, Ontario L6T 2J3
 Tel: (905) 456-2033
 Fax: (905) 456-1015